

Samsung V-NAND SSD 980 PRO with Heatsink

2023 Data Sheet

Revision 2.0



LEGAL DISCLAIMER

SAMSUNG ELECTRONICS CO., LTD. RESERVES THE RIGHT TO CHANGE PRODUCTS, INFORMATION AND SPECIFICATIONS WITHOUT NOTICE.

Products and specifications discussed herein are provided for reference purposes only. All information discussed herein may change without notice and is provided on an “AS IS” basis, without warranties of any kind. This document and all information discussed herein remain the sole and exclusive property of Samsung Electronics Co., Ltd. No license of any patent, copyright, mask work, trademark or any other intellectual property right is granted under this document, by implication, estoppels or otherwise. Samsung products are not intended for use in life support, critical care, medical, safety equipment, or similar applications where product failure could result in loss of life or personal or physical harm, or any military or defense application, or any governmental procurement to which special terms or provisions may apply. For updates or additional information about Samsung products, contact your nearest Samsung representative. All brand names, trademarks and registered trademarks belong to their respective owners.

COPYRIGHT © 2023

This material is copyrighted by Samsung Electronics Co., Ltd. Any unauthorized reproductions, use or disclosure of this material, or any part thereof, is strictly prohibited and is a violation under copyright law.

TRADEMARKS & SERVICE MARKS

The Samsung logo is the trademark of Samsung Electronics Co., Ltd. All other company and product names may be trademarks of the respective companies with which they are associated.

For more information, please visit www.samsung.com/ssd and www.samsungssd.com.

To download the latest software & manuals, please visit www.samsung.com/samsungssd

TECHNICAL SPECIFICATIONS

Samsung SSD 980 PRO with Heatsink					
Usage Application	Client PCs				
Interface	PCIe Gen 4.0 x4, NVMe 1.3c				
Hardware Information	Capacity ¹⁾		1TB	2TB	
	Controller		Samsung in-house Controller		
	NAND Flash Memory		Samsung V-NAND 3bit MLC		
	DRAM Cache Memory		1GB LPDDR4	2GB LPDDR4	
	Dimension		Max 80.15 x Max 25 x Max 8.88 (mm)		
	Form Factor		M.2 (2280)		
Performance (Up to.) ^{2) 3) 4)}	Sequential Read		7,000 MB/s	7,000 MB/s	
	Sequential Write		5,000 MB/s	5,100 MB/s	
	QD 1 Thread 1	Ran. Read	22K IOPS	22K IOPS	
		Ran. Write	60K IOPS	60K IOPS	
	QD 32 Thread 16	Ran. Read	1,000K IOPS	1,000K IOPS	
		Ran. Write	1,000K IOPS	1,000K IOPS	
Power Consumption (Up to) ⁵⁾	Idle (ASPT on)		35mW		
	Active (Avg.)	Read	6.2 W	6.1W	
		Write	5.7 W	5.6W	
	L1.2 mode		5 mW		
Reliability	Temp.	Operating	0°C to 70°C (Measured by S.M.A.R.T. Temperature Proper airflow recommended)		
		Non-Operating	-40°C to 85°C		
	Humidity		5% to 95% non-condensing		
	Shock	Non-Operating	1,500G(Gravity), duration: 0.5ms, 3 axis		
	Vibration	Non-Operating	20~2,000Hz, 20G		
	MTBF		1.5 million hours		
	Warranty ⁶⁾	TBW		600TB	1,200TB
Period		5 years limited			
Supporting Features	TRIM (Required OS support), Garbage Collection, S.M.A.R.T				
Data Security	AES 256-bit Full Disk Encryption, TCG/Opal V2.0, Encrypted Drive (IEEE1667)				

- 1) 1GB = 1,000,000,000 bytes by IDEMA. A certain portion of capacity may be used for system file and maintenance use, thus the actual available capacity may differ from the labeled capacity.
- 2) 980 PRO with Heatsink is backward compatible with PCIe 3.0. Sequential performances (up to): 3500 MB/s for reads, 3450 MB/s (1TB), 3470MB/s (2TB) for writes. Random performances (up to): 690K IOPS (1TB), 680K IOPS (2TB) for reads, 660K IOPS (1TB), 630K IOPS (2TB) for writes.
- 3) Sequential and random performance measurements are based on IOMeter1.1.0. Performance may vary based on SSD's firmware version, system hardware & configuration. Test System: AMD Ryzen 9 3900X 12-Core Processor CPU@3.79GHz, DDR4 2666MHz 16GBx2, OS-Windows 10 Pro 64bit, Chipset-ASUS-X570-ROG CROSSHAIR VIII FORMULA
- 4) Sequential and random write performance was measured with Intelligent TurboWrite technology being activated. Intelligent TurboWrite operates only within a specific data transfer size. For detailed information, please contact your local service center
- 5) Power consumption is measured with IOMeter1.1.0 version with AMD Ryzen 7 3700X 8 Core @3.6GHz, DDR4 8GBx2, OS-Windows 10 Pro 64bit, Chipset-GIGABYTE-X570-AORUS MASTER
- 6) Samsung's warranty will be void if any of the following instructions violated.
 - When assembling the 980 PRO, do not overtighten the 980 PRO with Heatsink to the motherboard.
 - The 980 PRO with Heatsink has a pre-installed heat sink and it should not be removed as it can damage the device.
 - The max dimensions of the 980 PRO with Heatsink with heatsink are 80.15 mm [L] x 25 mm [W] x 8.88 mm [H]. Please check your host system provides sufficient space for installation in advance.
 - Product warranty will be void if a heatsink is removed from 980 PRO with Heatsink.
- 7) All documented endurance test results are in compliance with JEDEC218 Standards. Please visit www.jedec.org for detailed information on JEDEC218 Standards. TBW means Terabytes Written, Warranty provides coverage for the stated time period or the TBW, whichever comes first. Please refer to the detailed warranty statement here at <http://www.samsung.com/samsungssd>

PRODUCT LINEUP

Density	Model Name	Box Contents	Model Code
1TB (1,000GB*)	MZ-V8P1T0	Samsung SSD 980 PRO with Heatsink 1TB Warranty Statement	MZ-V8P1T0CW
2TB (2,000GB*)	MZ-V8P2T0	Samsung SSD PRO with Heatsink PRO 2TB Warranty Statement	MZ-V8P2T0CW

* GB: 1GB = 1,000,000,000 bytes. The actual usable capacity may be less than the labeled capacity.

For more information, including but not limited to the warranty provided for this product, and to download the latest software & manuals, please visit www.samsung.com/ssd and www.samsungssd.com

TEST CONFIGURATION

Below you will find a list of system configurations Samsung used to obtain the results reported in this Data Sheet. All performance data was measured with the SSD as a secondary drive

	Read/Write Performance	Power Consumption
Interface	PCIe Gen 4.0 x4	PCIe Gen 4.0 x4
OS	Windows 10 Pro 64bit	Windows 10 Pro 64bit
CPU	AMD Ryzen 9 3900X 12-Core CPU@3.79GHz	AMD Ryzen 7 3700X 8 Core @3.6GHz
Memory	DDR4 2666MHz 16GBx2	DDR4 8GBx2
Chipset	ASUS-X570-ROG CROSSHAIR VIII FORMULA v	GIGABYTE-X570-AORUS MASTER
Test Program	IOmeter 1.1.0	IOmeter 1.1.0

The test values in the review were obtained under the following BIOS settings.

- 1) BIOS version: 1201(2019/11/18)
- 2) Advanced/AMD CBS/CPU Common Options/Global C-state Control: Auto -> Disabled
- 3) Overclock
 - 3-1) Ai Overclock Tuner: Default -> Manual
 - 3-2) Memory Frequency: Auto -> DDR4-3600MHz
 - 3-3) Core Performance Boost: Auto -> Disabled
 - 3-4) CPU Core Ratio: Auto -> 43.75
 - 3-5) Precision Boost Overdrive/Precision Boost Overdrive: Auto -> Disabled
 - 3-6) DRAM Timing Control/DRAM CAS# Latency: Auto -> 17
 - DRAM Timing Control/Trcdrd : Auto -> 19
 - DRAM Timing Control/Trcdwr : Auto -> 19
 - DRAM Timing Control/DRAM RAS# PRE Time: Auto -> 18
 - DRAM Timing Control/DRAM RAS# ACT Time: Auto -> 36
 - 3-7) DRAM Voltage: Auto -> 1.35

Revision History

Revision Number	Description	Revision Date
1.0	Initial Release	October, 2021
2.0	Heatsink Max Dimension Revised	June, 2023